

MATERIAL SAFETY DATA SHEET

CNH Tutela L-7283 Polyurea Grease

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

TRADE NAME	CNH Tutela L-7283 Polyurea Grease
PART No.	
PRODUCT USE	Lubricating Grease
SUPPLIER	Viscosity Oil Co. Willowbrook, IL 60527 Phone:630-850-4000 Fax:: 630-850-4023
EMERGENCY TELEPHONE	Chemtrec U.S. (800) 424-9300 Outside the U.S.- 001-703-527-3887

2. COMPOSITION, INFORMATION ON INGREDIENTS

INGREDIENT NAME	CAS No.	WEIGHT
DISTILLATES, PETROLEUM, SOLVENT-REFINED HEAVY PARAFFINIC RESIDUAL OILS, PETROLEUM, SOLVENT-REFINED	64741-88-4	30-50 %
DISTILLATES, PETROLEUM, HYDROTREATED HEAVY NAPHTHENIC	64742-01-4	10-30%
POLYUREA THICKENER (PROPRIETARY INGREDIENT# 28317)	64742-52-5	10-30%
GEAR OIL ADDITIVE (PROPRIETARY INGREDIENT# 28320)	Proprietary	10-30% 1-
	Proprietary	1-5 %

COMPOSITION COMMENTS

Refer to section eight for exposure limits on ingredients.
Chemical ingredients not regulated by OSHA or SARA are treated confidentially.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Exposure to vapors generated at high temperatures, may cause respiratory irritation.

ACUTE EFFECTS

CHRONC EFFECTS

SENSITIZATION	No known information.
CARCINOGENICITY	IARC: Not listed. OSHA: Not regulated. NTP: Not listed.

HEALTH WARNINGS

INHALATION. Heating can generate vapors that may cause respiratory irritation, nausea and headaches. Inhalation hazard at room temperature is unlikely due to the low volatility of this product. SKIN CONTACT. Repeated or prolonged contact can result in drying of the skin. EYE CONTACT. Irritating. INGESTION. Can cause stomach ache and vomiting. Main hazard, if ingested, is aspiration into the lungs and subsequent pneumonitis.

OTHER INFORMATION

ROUTE OF ENTRY

Inhalation. Skin and/or eye contact. Ingestion.

MEDICAL SYMPTOMS

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Not determined

4. FIRST AID MEASURES

INHALATION

Vapor inhalation under ambient conditions is normally not a problem. If overcome by vapor of hot product, immediately remove from source of exposure. Move the exposed person to fresh air at once. For breathing difficulties oxygen may be necessary. Get medical attention if any discomfort continues.

EYES

Rinse the eye with water immediately. Continue to rinse for at least 15 minutes. Contact physician if discomfort continues.

SKIN

Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

INGESTION

DO NOT INDUCE VOMITING! Get medical attention immediately!

5. FIRE FIGHTING MEASURES

FLASH POINT (°C)

246 Cd OC (Cleveland open cup).

FLAMMABILITY LIMIT -

NID

LOWER(%)

FLAMMABILITY LIMIT -

NID

UPPER(%)

EXTINGUISHING MEDIA

Use: Carbon dioxide (CO2). Dry chemicals, sand, dolomite etc. Alcohol resistant foam. Water spray, fog or mist.

SPECIAL FIRE FIGHTING PROCEDURES

Use water to keep fire exposed containers cool and disperse vapors. Water spray may be used to flush spills away from exposures and dilute spills to non-flammable mixtures. Avoid water in straight hose stream; will scatter and spread fire. Keep run-off water out of sewers and water sources. Dike for water control.

UNUSUAL FIRE & EXPLOSION HAZARDS

Pressure will increase in over heated, closed containers.

HAZARDOUS COMBUSTION PRODUCTS

Acrid smoke/fumes. Oxides of: Carbon. Nitrogen.

PROTECTIVE MEASURES IN CASE OF FIRE

Self-contained breathing equipment and chemical resistant clothing recommended.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS	Minimize skin contact.
PRECAUTIONS TO PROTECT THE ENVIRONMENT	Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses or extensive land areas. Assure conformity with applicable government regulations.
SPILL CLEAN-UP PROCEDURES	Keep all sources of ignition and hot metal surfaces away from spill. Avoid contact with eyes or skin. Place leaking containers in well ventilated area. If fire potential exists, blanket spill with foam or use water spray to disperse vapors. Contain spill to minimize contaminated area and facilitate salvage or disposal. To clean up spill, flush area sparingly with water or use absorbant material. A void discharge to natural water ways.

7. HANDLING AND STORAGE

HANDLING PRECAUTIONS	Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapors. Use approved respirator if air contamination is above accepted level. Do not reuse container. Keep lid closed when not in use. Do not store or mix with strong oxidizers. A void spilling, skin and eye contact. Eye wash and emergency shower must be available at the work place.
STORAGE PRECAUTIONS	Store separate from strong acids and oxidizers. Keep away from heat, sparks and open flame.
STORAGE CRITERIA	Chemical storage.

8. EXPOSURE CONTROLS, PERSONAL PROTECTION

COMPONENT	STD	TWA	STEL	TWA	STEL
DISTILLATES, PETROLEUM, SOLVENT-REFINED HEAVY PARAFFINIC	OSHA			5 mg/m3 ^{**} (1)	
RESIDUAL OILS, PETROLEUM, SOLVENT-REFINED	ACGIH			5 mg/m3 ^{**} (1)	10 mg/m3 ^{**} (1)
DISTILLATES, PETROLEUM, HYDROTREATED HEAVY NAPHTHENIC	OSHA			5 mg/m3 ^{**} (1)	
	ACGIH			5 mg/m3 ^{**} (1)	10 mg/m3 ^{**} (1)
	ACGIH			5 mg/m3 ^{**} (1)	10 mg/m3 ^{**} (1)

INGREDIENT COMMENTS

^{**}(1) For respirable oil mist.

PROTECTIVE EQUIPMENT



ENGINEERING CONTROLS	Use engineering controls to reduce air contamination to permissible exposure level.
VENTILATION	No specific ventilation requirements noted, but forced ventilation may still be required if air contamination exceeds acceptable level.
RESPIRATORS	No specific recommendation made, but respiratory protection may still be required under exceptional circumstances when excessive air contamination exists.
PROTECTIVE GLOVES	Chemical resistant gloves recommended to prevent prolonged or repeated contact.
EYE PROTECTION	Wear splash-proof eye goggles to prevent any possibility of eye contact.
PROTECTIVE CLOTHING	Wear appropriate clothing to prevent repeated or prolonged skin contact.
HYGIENIC WORK PRACTICES	Wash at the end of each work shift and before eating, smoking and using the toilet.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE/PHYSICAL STATE	Grease.		
COLOR	Blue green.		
ODOR	Mild (or faint). Petroleum.		
SOLUBILITY DESCRIPTION	Insoluble in water.		
DENSITY	0.89	Temperature (°C)	16
VAPOR DENSITY (air=1)	>5		
VAPOR PRESSURE	<0.01 mmHg	Temperature (°C)	20
EVAPORATION RATE	<0.01	Reference	BuAc=1
pH-VALUE, CONC. SOLUTION	N/A		

10. STABILITY AND REACTIVITY

STABILITY	Normally stable.
CONDITIONS TO AVOID	Avoid contact with acids and oxidizing substances.
HAZARDOUS POLYMERIZATION	Will not occur.
POLYMERIZATION DESCRIPTION	Not applicable

**HAZARDOUS
DECOMPOSITION PRODUCTS**

Oxides of: Carbon.

11. TOXICOLOGICAL INFORMATION

**TOXICOLOGICAL
INFORMATION**

No experimental toxicological data on the preparation as such is available.

12. ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION

There is no ecological data on the product itself.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Spilled material, unused contents and empty containers must be disposed of in accordance with local, state and federal regulations.

14. TRANSPORT INFORMATION

**DOT HAZARD CLASS
IDENTIFICATION No.**

Non-Hazardous (No label required).
N/A

SEA TRANSPORT NOTES

Not regulated.

AIR TRANSPORT NOTES

Not regulated.

15. REGULATORY INFORMATION

COMPONENT	US FEDERAL REGULATIONS		
	SARA 302	CERCLA	SARA 313
RESIDUAL OILS, PETROLEUM, SOLVENT-REFINED	N/A	N/A	N/A
DISTILLATES, PETROLEUM, HYDROTREATED HEAVY NAPHTHENIC	N/A	N/A	N/A
POLYUREA THICKENER (PROPRIETARY INGREDIENT #28317)	N/A	N/A	N/A
GEAR OIL ADDITIVE (PROPRIETARY INGREDIENT# 28320)	N/A	N/A	N/A
DISTILLATES, PETROLEUM, SOLVENT-REFINED HEAVY PARAFFINIC	N/A	N/A	N/A

REGULATORY STATUS

None.

CLEAN AIR ACT

US STATE REGULATI

WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM – WHIMIS

INVENTORIES

COMPONENT	CAN	US	EU	AUS	JAP	KOR	CHN	PHLP
DISTILLATES, PETROLEUM, SOLVENT-REFINED HEAVY PARAFFINIC	DSL	YES	EINECS	YES	YES	YES	YES	
RESIDUAL OILS, PETROLEUM, SOLVENT-REFINED DISTILLATED, PEROLEUM, HYDROTREATED HEAVY NAPHTHENIC	DSL	YES	EINECS	YES	YES	YES	YES	
POYUREA THICKENER (PROPRIETARY INGREDIENT# 28317)	DSL	YES	EINECS	No	Exempt	No	No	
GEAR OIL ADDITIVE (PROPRIETARY INGREDIENT# 28320)	DSL	YES	EINECS		YES			

NOTICE: This product contains one or more components that are NOT LISTED on the following Inventories:
 Australia AICS
 Korea ECL
 Phillipines PICCS

16. OTHER INFORMATION

HEALTH Irritation, minor residual injury (1) – HMIS/NFPA
FLAMMABILITY Burns only if pre-heated (1) – HMIS/NFPA
REACTIVITY Normally Stable (0) - HMIS/NFPA
REVISION COMMENTS Section 2: Ingredients
 Section 15: Inventory Status

PREPARED BY

REVISION No./Repl. MSDS of 2002-02-12

DATE 2007-06-08

DISCLAIMER

While the information and recommendations set forth herein are believed to be accurate as of the Date thereof, FL Viscosity makes no warranty with respect thereto and disclaims all liability from reliance therein.