



# Tutela Hydraulic Excavator Fluid

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations  
Date of issue: 10/09/2015 Version: 1.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixture  
Product name : Tutela Hydraulic Excavator Fluid

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Lubricant

### 1.3. Details of the supplier of the safety data sheet

Viscosity Oil Company  
600 H Joliet Road  
Willowbrook, IL 60527  
T 630-850-4000 - F 630-850-4022

### 1.4. Emergency telephone number

Emergency number : (800) 434-9300  
CHEMTREC (24 HOURS)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### GHS-US classification

Not classified

### 2.2. Label elements

#### GHS-US labelling

No labelling applicable

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

0.07 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)  
0.11 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)  
0.86 percent of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO < 3%)	(CAS No) 64742-65-0	0 – 90	Asp. Tox. 1, H304
Calcium sulfonate	(CAS No) trade secret	0 – 0.9	Skin Sens. 1B, H317
2,6-di-tert-butylphenol	(CAS No) 128-39-2	0.1 – 0.5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Gently wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.  
First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water.  
First-aid measures after ingestion : Do NOT induce vomiting. Get medical advice/attention.

# Tutela Hydraulic Excavator Fluid

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Inhalation of vapours may cause respiratory irritation.
Symptoms/injuries after skin contact	: Repeated or prolonged contact may cause skin irritation.
Symptoms/injuries after eye contact	: May cause slight irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

---

### 5.1. Extinguishing media

Suitable extinguishing media	: Water fog. Foam. Carbon dioxide. Dry powder.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Burning produces irritating, toxic and noxious fumes.
Explosion hazard	: Product is not explosive.
Reactivity	: No dangerous reactions known.

### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

## SECTION 6: Accidental release measures

---

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid all eye and skin contact and do not breathe vapour and mist.
------------------	--

#### 6.1.1. For non-emergency personnel

Protective equipment	: Wear suitable gloves.
Emergency procedures	: Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment	: Wear suitable gloves.
Emergency procedures	: Stop leak if safe to do so. Ventilate area.

### 6.2. Environmental precautions

Avoid release to the environment. Do not discharge into drains or the environment.

### 6.3. Methods and material for containment and cleaning up

For containment	: Do not allow minor leaks or spills to accumulate on walking surfaces. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Absorb and/or contain spill with inert material, then place in suitable container.

### 6.4. Reference to other sections

Section 8: personal protective equipment.

## SECTION 7: Handling and storage

---

### 7.1. Precautions for safe handling

Precautions for safe handling	: Avoid all eye and skin contact and do not breathe vapour and mist.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep container tightly closed.
Incompatible products	: Strong oxidizers.
Incompatible materials	: Heat sources.
Heat and ignition sources	: Keep away from heat, sparks and flame.
Storage area	: Store in dry, cool, well-ventilated area.

### 7.3. Specific end use(s)

Lubricant.

# Tutela Hydraulic Excavator Fluid

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Tutela Hydraulic Excavator Fluid		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> oil mist
ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> oil mist
OSHA	Not applicable	
Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO < 3%) (64742-65-0)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
2,6-di-tert-butylphenol (128-39-2)		
ACGIH	Not applicable	
OSHA	Not applicable	
Calcium sulfonate (trade secret)		
ACGIH	Not applicable	
OSHA	Not applicable	

#### 8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear suitable gloves.
Eye protection	: In case of splashing or aerosol production: protective goggles.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. NIOSH. Approved respirator.
Environmental exposure controls	: Prevent leakage or spillage. Prevent contaminated water run-off.
Other information	: Do not eat, drink or smoke when using this product.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Blue
Odour	: petroleum
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: -40 °C
Boiling point	: No data available
Flash point	: 190 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Vapour pressure	: < 1 mm Hg
Relative density	: 0.86
Relative vapour density at 20 °C	: No data available
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: 46 cSt @ 40 °C

# Tutela Hydraulic Excavator Fluid

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, dynamic : No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong oxidizers.

### 10.6. Hazardous decomposition products

Burning produces irritating, toxic and noxious fumes. hydrocarbons. Carbon oxides (CO, CO<sub>2</sub>). Nitrogen oxides. Phosphorus oxides. Sulphur oxides.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Likely routes of exposure : Inhalation, skin and eyes contact

Acute toxicity : Not classified

Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO < 3%) (64742-65-0)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : Inhalation of vapours may cause respiratory irritation.

Symptoms/injuries after skin contact : Repeated or prolonged contact may cause skin irritation.

Symptoms/injuries after eye contact : May cause slight irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology – water : Harmful to aquatic life with long lasting effects.

Calcium sulfonate (trade secret)	
LC50 fish 1	> 1000 mg/l 4 d Fathead minnow
EC50 Daphnia 1	> 1000 mg/l 2 d
EC50 other aquatic organisms 1	> 1000 mg/l 4 d Green algae
LC50 fish 2	> 10000 mg/l 4 d Sheepshead minnow

### 12.2. Persistence and degradability

Tutela Hydraulic Excavator Fluid	
Persistence and degradability	May cause long-term adverse effects in the environment.

Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO < 3%) (64742-65-0)	
Persistence and degradability	Not established.

# Tutela Hydraulic Excavator Fluid

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.3. Bioaccumulative potential

<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO &lt; 3%) (64742-65-0)</b>	
Bioaccumulative potential	Not established.

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.  
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.  
Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Not considered a dangerous good for transport regulations

### Additional information

Other information : No supplementary information available.

### ADR

No additional information available

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO &lt; 3%) (64742-65-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>2,6-di-tert-butylphenol (128-39-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

### 15.2. International regulations

#### CANADA

<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO &lt; 3%) (64742-65-0)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
<b>2,6-di-tert-butylphenol (128-39-2)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	

#### EU-Regulations

<b>Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO &lt; 3%) (64742-65-0)</b>	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
<b>2,6-di-tert-butylphenol (128-39-2)</b>	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aquatic Chronic 3 H412

Full text of hazard classes and H-statements : see section 16

### National regulations

# Tutela Hydraulic Excavator Fluid

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO < 3%) (64742-65-0)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on KECI (Korean Existing Chemicals Inventory)  
Listed on Taiwan National Chemical Inventory  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

### 15.3. US State regulations

No additional information available


## SECTION 16: Other information

Indication of changes	: Original Document.
Data sources	: ACGIH (American Conference of Government Industrial Hygienists). European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <a href="http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database">http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database</a> . Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. NIOSH Occupational Health Guide for chemical Substances - Vol. II, September, 1978. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at <a href="http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html">http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html</a> .
Abbreviations and acronyms	: CAS (Chemical Abstracts Service) number. CFR: Code of Federal Regulations. CLP: Classification, Labelling, Packaging. GHS: Globally Harmonized System (of Classification and Labeling of Chemicals). OSHA: Occupational Safety & Health Administration. TSCA: Toxic Substances Control Act.
Other information	: None.

Full text of H-statements:

Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1B	Sensitisation — Skin, category 1B
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

NFPA health hazard	: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.
NFPA fire hazard	: 1 - Must be preheated before ignition can occur.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Redstone SDS US GHS for Viscosity Oil

**SDS Prepared by:** The Redstone Group, LLC  
6077 Frantz Rd.  
Suite 206  
Dublin, OH 43016  
T 614-923-7472  
[www.redstonegrp.com](http://www.redstonegrp.com)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*