



VISCOSITY

## Product Data Sheet

Revised: 2022/01/22 (version 6)

# VISCOSITY UNITEK MG SAE 30 Gasoline & Diesel Engine Oil

Engineered with Fluid Technology Solutions™, our expertly designed formulation provides high performance and an extended protection for your off-road equipment.

Your number one priority is making sure your off-road equipment is always on the move. It's the engine of your business! When your equipment operates in the most extreme conditions, there are three main enemies that could keep you from meeting your commitments: **Engine Deposits, Viscosity Control and Corrosion**. All three are aggravated by farming's severe operating conditions and can cause **unplanned downtime**.



### Description and Applications



Severe Duty  
Protection



Wear  
Protection



Rust &  
Corrosion  
Protection

**VISCOSITY UNITEK MG GASOLINE AND ENGINE OIL SAE 30** is formulated with high quality base oils and lower ash for gasoline and older diesel engines.

UNITEK MG is formulated with high quality detergents and base oils to protect your engine from wear, oxidation, and corrosion. It is recommended for use where API CF, API SL, or legacy "low ash" engine oil are recommended or required.

### Benefits

- **Excellent** Deposit & Soot Control.
- **Excellent** Wear Protection.
- **Excellent** Oxidation Control.
- **Excellent** Corrosion Protection.
- **For use in "low ash" agriculture equipment applications.**

### Approvals, Specifications and Recommendations

**VISCOSITY UNITEK MG Gasoline and Diesel Engine Oil SAE 30 CF-2/CF** is a lubricant that meets the following performances:

#### Approvals and Specifications:

- API CF, SL.
- MAT 3622

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your specific vehicle

## Typical Physical Data

Parameters	Method	Unit	Typical Value
<b>Kinematic Viscosity, 100C, cst</b>	ASTM D445	cSt	10.5 (Min)
<b>Viscosity Index</b>	ASTM D2270		110
<b>Pour Point, C</b>	ASTM D97	°C	-25
<b>Flash Point, C</b>	ASTM D92	°C	240
<b>Phosphorus, Mass %</b>	ASTM D4951	Mass %	0.10
<b>Zinc, Mass %</b>	ASTM D4951	Mass %	0.12 (Max)
<b>Sulfur, Mass %</b>	ASTM D4951	Mass %	0.40 (Max)
<b>Total Base Number (TBN)</b>	ASTM D2896	TBN	8.5 (Min)
<b>Specific Gravity @15.6C</b>	ASTM D1298		0.880

All technical data is provided for reference only. These characteristics are typical of current production. Whilst future production will conform to VISCOSITY's specification, variations in these characteristics may occur.

### Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water. For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: [www.viscosityoil.com](http://www.viscosityoil.com)

### Important Note

VISCOSITY Documents and the information contained herein is believed to be accurate as of the date of printing. VISCOSITY Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these VISCOSITY Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either VISCOSITY or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.