



VISCOSITY

Product Data Sheet

Revised: 2020/11/24 (version 8)

VISCOSITY ACTIFULL OT Coolant Organic

Engineered with Fluid Technology Solutions™, our expertly designed formulation provides high performance and an extended protection for your off-road equipment.

Your number one priority is making sure your off-road equipment is always on the move. It's the engine of your business! When your equipment operates in the most extreme conditions - it requires premium heat handling for the most reliable performance.



Description and Applications

VISCOSITY ACTIFULL OT Coolant Organic is an advanced coolant engineered for the higher operating temperatures running in Tier 4B engines required *to keep your work in fluid motion*.



NO SCA's



Temperature
Control

VISCOSITY ACTIFULL OT Coolant Organic is an organic acid, ethylene glycol-based product. **This product does not require an initial charge of supplemental coolant additive** and is specially formulated to protect heavy-duty diesel wet sleeve liners. Contains organic corrosion inhibitors that do not degrade over the course of the drain interval, helping to **prevent rust and protecting your cooling system even in extreme temperatures**.

Benefits

VISCOSITY ACTIFULL OT Coolant Organic enhances your business profits and your vehicle availability while significantly reducing your operating costs through:

- **Best cooling capacity** by resisting scale formation common with conventional coolants which impede **heat removal** from piston liners.
- **Best pitting** resistance to protect engine liners
- **Outstanding corrosion protection** throughout the cooling system ensuring **longevity of engine components**
- **Extended life** due to the use organic corrosion inhibitors which do not de overtime
- **Compatible** with most commonly used elastomer seals in diesel engines
- **Eliminates the cost of SCAs, test strips and manpower** required to test the coolant and add SCA

Approvals, Specifications and Recommendations

VISCOSITY ACTIFULL OT Coolant Organic is an advanced coolant engineered with organic corrosion inhibitors and ethylene glycol based anti-freeze/anti-boil combined to protect the hottest running Tier 4B engines that meets below performances:

Approvals and Specifications:

- MAT 3724
- MAT 3624
- FIAT 9.55523
- ASTM D6210, ASTM D3306
- Cummins 14603
- Chrysler MS 12106

Note: Always consult your owner's manual to check recommended fluid and specifications for your specific vehicle/equipment

Typical Physical Data *When Diluted

Parameters	ASTM Method	Unit	Typical Value
% Water	D1123	%	50.0
Reserve Alkalinity	D1121	mg KOH/g	4.5
Specific Gravity @15.5C	D1122		1.07
Glassware Corrosion	D1384		Pass
Boiling Point	D1120	C	108
pH	D1287		8.3
Freezing Point	D1177	C	-37
Color	Visual		Red

All technical data is provided for reference only. These characteristics are typical of current production. Whilst future production will conform to VISCOSITY's specification, variations in these characteristics may occur.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water. For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.viscosityoil.com

Important Note

VISCOSITY Documents and the information contained herein is believed to be accurate as of the date of printing. VISCOSITY Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these VISCOSITY Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either VISCOSITY or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.