



VISCOSITY

Product Data Sheet

Revised: 2020/12/21 (Version 2)

VISCOSITY TUTELA DIESEL FUEL SYSTEM CLEANER

Engineered with Fluid Technology Solutions™, our expertly designed formulation provides high performance and an extended protection for your off-road equipment.

Your number one priority is making sure your equipment is always on the move. It's the engine of your business! When your equipment operates in the most extreme conditions- it requires the best protection available.



Description and Applications

VISCOSITY TUTELA Diesel Fuel System Cleaner is formulated to protect the diesel fuel storage in tanks from fuel degradation to keep your farm in fluid motion.



Fuel Economy



System Cleaner

VISCOSITY TUTELA Diesel Fuel System Cleaner is a multifunctional additive that helps keep your fuel system clean, improves combustion, provides for smoother engine operation, and can restore power loss and provide increase in fuel economy. Suitable for all the latest generation engines. Recommended to be used every 200 hours for maximum benefits.

Benefits

- **Removes** fuel injector **deposits**
- **Lengthens engine life** and **prevents fuel injector deposit** formation with regular use.
- Helps **reduce power loss**
- **Reduces emissions** and exhaust fumes.
- **Increases fuel economy**
- **Increases fuel cetane** number by up to 2 points
- **Increases lubricity** and **extends fuel pump's life**
- **Increases fuel stability** and **prevents fuel system corrosion** and **sludge formation**

Typical Physical Data

Parameters	Method	Typical Value
Appearance	Visual	Slight Haze
Specific Gravity	ASTM D4052	0.87
Gardner Color	ASTM D1544	10
Refractive Index	ASTM D1218	1.46

All technical data is provided for reference only. These characteristics are typical of current production. Whilst future production will conform to VISCOSITY's specification, variations in these characteristics may occur.

Health, Safety and Environment



VISCOSITY

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water. For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.viscosityoil.com

Important Note

VISCOSITY Documents and the information contained herein is believed to be accurate as of the date of printing. VISCOSITY Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these VISCOSITY Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either VISCOSITY or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.