

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : VISCOSITY ACTIFULL OT Coolant Organic Premix (3x1G)

1.2. Recommended use and restrictions on use

Recommended use : Coolant
Restrictions on use : No data available

1.3. Supplier

Supplier

Viscosity Oil Company
600 H Joliet Road
Willowbrook, IL 60527
T 630-850-4000 - F 630-850-4022

Importer

Viscosity Oil Company
1918 Boul.Saint-Regis
Dorval, QC H9P 1H6 - Canada

1.4. Emergency telephone number

Emergency number : (800) 424-9300
CHEMTREC (24 HOURS)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Acute toxicity (oral), Category 4	H302	Harmful if swallowed.
Specific target organ toxicity — Repeated exposure, Category 2	H373	May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS labelling

Hazard pictograms (GHS) : 

Signal word (GHS) : Warning

Hazard statements (GHS) : H302 - Harmful if swallowed.
H373 - May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

Precautionary statements (GHS) : P260 - Do not breathe mist, spray, vapours.
P264 - Wash hands thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P301+P312 - If swallowed: Call a doctor if you feel unwell.
P314 - Get medical advice/attention if you feel unwell.
P330 - Rinse mouth.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No data available

2.4. Unknown acute toxicity (GHS)

4.29% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
4.29% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
4.29% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

VISCOSITY ACTIFULL OT Coolant Organic Premix (3x1G)

Safety Data Sheet

Hazardous Products Regulations (SOR/2015-17) / Règlement sur les produits dangereux (DORS/2015-17)

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	% (w/w)	GHS classification
Ethylene glycol	CAS-No.: 107-21-1	40 - 50	Acute Tox. 4 (Oral), H302 STOT RE 2, H373

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: If medical advice is needed, have product container or label at hand.
First-aid measures after inhalation	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Rinse immediately contaminated clothing and skin with plenty of water before removing clothes. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion	: Drink plenty of water. Do NOT induce vomiting unless directed to do so by medical personnel.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
Symptoms/effects after skin contact	: May cause slight irritation.
Symptoms/effects after eye contact	: May cause slight irritation.
Symptoms/effects after ingestion	: Harmful if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

4.3. Immediate medical attention and special treatment, if necessary

All treatments should be based on observed signs and symptoms of distress in the patient.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: carbon dioxide (CO ₂), powder, alcohol-resistant foam, water fog.
Unsuitable extinguishing media	: None known.

5.2. Specific hazards arising from the chemical

Fire hazard	: No particular fire or explosion hazard.
-------------	---

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Do not allow run-off from fire fighting to enter drains or water courses.
Protection during firefighting	: Wear a self contained breathing apparatus. Wear fire/flammable resistant/retardant clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid all eye and skin contact and do not breathe vapour and mist. Use personal protective equipment as required.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Refer to section 8.2.
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Refer to section 8.2.
Emergency procedures	: Stop leak if safe to do so.

6.2. Environmental precautions

Do not discharge into drains or the environment.

VISCOSITY ACTIFULL OT Coolant Organic Premix (3x1G)

Safety Data Sheet

Hazardous Products Regulations (SOR/2015-17) / Règlement sur les produits dangereux (DORS/2015-17)

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Exclude sources of ignition and ventilate the area. Small spills: Wipe up with absorbent material (e.g. cloth, fleece). Impound and recover large spill by mixing it with inert granular solids.

6.4. Reference to other sections

Section 7: safe handling. Section 8: personal protective equipment. Section 13: disposal information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapour and mist. Use only outdoors or in a well-ventilated area. Wear personal protective equipment.
- Hygiene measures : Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Protect from moisture. Keep only in the original container. Keep container closed when not in use.
- Incompatible materials : Strong acids. Strong bases. Strong oxidizers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

VISCOSITY ACTIFULL OT Coolant Organic Premix (3x1G)	
No data available	
Ethylene glycol (107-21-1)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethylene glycol
ACGIH OEL TWA [ppm]	25 ppm (V - Vapor fraction)
ACGIH STEL (mg/m ³)	10 mg/m ³ (I - Inhalable particulate matter, H - Aerosol only)
ACGIH OEL STEL [ppm]	50 ppm (V - Vapor fraction)
ACGIH OEL C	100 mg/m ³
ACGIH OEL C [ppm]	39.4 ppm
Remark (ACGIH)	TLV® Basis: URT irr. Notations: A4 (Not classifiable as a Human Carcinogen)
Regulatory reference	ACGIH 2020
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL C [ppm]	50 ppm

8.2. Appropriate engineering controls

- Appropriate engineering controls : Avoid creating mist or spray. Avoid splashing. Either local exhaust or general room ventilation is usually required. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
- Environmental exposure controls : Prevent contaminated water run-off. Prevent leakage or spillage.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration. nitrile rubber gloves. Butyl rubber

VISCOSITY ACTIFULL OT Coolant Organic Premix (3x1G)

Safety Data Sheet

Hazardous Products Regulations (SOR/2015-17) / Règlement sur les produits dangereux (DORS/2015-17)

Eye protection:

In case of splashing or aerosol production: protective goggles.

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. If needed, use an air-purifying respirator with organic vapor cartridges and a dust/mist prefilter.

Other information:

Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: liquid.
Colour	: Yellow
Odour	: chemical odor
Odour threshold	: No data available
pH	: 7.9
Melting point	: -37 °C
Freezing point	: -37 °C
Boiling point	: 109 °C
Flash point	: 120 °C
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 1.07
Solubility	: Material highly soluble in water.
Log Pow	: -1.36
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: < 10 mm ² /s @ 20 °C
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂).

VISCOSITY ACTIFULL OT Coolant Organic Premix (3x1G)

Safety Data Sheet

Hazardous Products Regulations (SOR/2015-17) / Règlement sur les produits dangereux (DORS/2015-17)

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

VISCOSITY ACTIFULL OT Coolant Organic Premix (3x1G)

ATE (oral)	1042.949 mg/kg bodyweight
Unknown acute toxicity (GHS)	4.29% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 4.29% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 4.29% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

Ethylene glycol (107-21-1)

LD50 dermal rat	> 3500 mg/kg (mouse)
LC50 Inhalation - Rat	> 2.5 mg/l/4h
ATE (oral)	500 mg/kg bodyweight

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

Ethylene glycol (107-21-1)

LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight/day
NOAEL (oral, rat, 90 days)	150 mg/kg bodyweight/day kidney
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified
Viscosity, kinematic : < 10 mm²/s @ 20 °C
Likely routes of exposure : Inhalation. Skin and eye contact.
Symptoms/effects : May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
Symptoms/effects after skin contact : May cause slight irritation.
Symptoms/effects after eye contact : May cause slight irritation.
Symptoms/effects after ingestion : Harmful if swallowed. Swallowing a small quantity of this material will result in serious health hazard.

SECTION 12: Ecological information

12.1. Toxicity

Ethylene glycol (107-21-1)

LC50 fish 1	72860 mg/l Pimephales promelas
EC50 crustacea	> 100 mg/l
NOEC chronic fish	15380 mg/l Pimephales promelas
NOEC chronic crustacea	8590 mg/l Ceriodaphnia sp.

12.2. Persistence and degradability

VISCOSITY ACTIFULL OT Coolant Organic Premix (3x1G)

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

VISCOSITY ACTIFULL OT Coolant Organic Premix (3x1G)

Safety Data Sheet

Hazardous Products Regulations (SOR/2015-17) / Règlement sur les produits dangereux (DORS/2015-17)

Ethylene glycol (107-21-1)	
Persistence and degradability	Readily biodegradable.
Biodegradation	> 60 % 28 d

12.3. Bioaccumulative potential

VISCOSITY ACTIFULL OT Coolant Organic Premix (3x1G)	
Log Kow	-1.36
Ethylene glycol (107-21-1)	
Log Pow	- 1.36
Bioaccumulative potential	Not expected to bioaccumulate.

12.4. Mobility in soil

VISCOSITY ACTIFULL OT Coolant Organic Premix (3x1G)	
Ecology - soil	No data available.

12.5. Other adverse effects

Other information : No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with Transportation of Dangerous Goods / IMDG / IATA

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (TDG) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable

14.3. Transport hazard class(es)

TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

14.4. Packing group

Packing group (TDG) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

TDG

No data available

VISCOSITY ACTIFULL OT Coolant Organic Premix (3x1G)

Safety Data Sheet

Hazardous Products Regulations (SOR/2015-17) / Règlement sur les produits dangereux (DORS/2015-17)

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

CANADA

Ethylene glycol (107-21-1)

Listed on the Canadian DSL (Domestic Substances List) inventory.

SECTION 16: Other information

Data sources : Canadian Centre for Occupational Health and Safety. Accessed at: http://www.ccohs.ca/oshanswers/legisl/whmis_classifi.html. European Chemicals Agency (ECHA) Registered Substances list. Accessed at <http://echa.europa.eu/>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. OSHA 29CFR 1910.1200 Hazard Communication Standard.

Other information : None.

Full text of H-statements

H302	Harmful if swallowed.
H373	May cause damage to organs through prolonged or repeated exposure.

Abbreviations and acronyms

	ACGIH (American Conference of Government Industrial Hygienists)
ATE	Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	TWA: Time Weighted Average

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.