



# VISCOSITY TUTELA Gear Oil SAE 85W-140

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Issue date: 08/08/2019

Revision date: 12/04/2020

Version: 2.0

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : VISCOSITY TUTELA Gear Oil SAE 85W-140

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Lubricant  
Restrictions on use : No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

Viscosity Oil Company  
600 H Joliet Road  
Willowbrook, IL 60527  
T 630-850-4000 - F 630-850-4022

##### Importer

Viscosity Oil Company  
1918 Boul.Saint-Regis  
Dorval, QC H9P 1H6 - Canada

#### 1.4. Emergency telephone number

Emergency number : (800) 424-9300  
CHEMTREC (24 HOURS)

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS classification

Not classified

#### 2.2. Label elements

##### GHS-US labelling

No labelling applicable

#### 2.3. Other hazards

No additional information available

#### 2.4. Unknown acute toxicity (GHS\_US)

1% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)  
1% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)  
1% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	% (w/w)	GHS classification
Long-chain alkyl amine (HMIRA Reg. No. 9939; Filing date 4/11/2016)	(CAS-No.) trade secret	0.1 - <1	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation), H330 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin thoroughly with mild soap and water. Wash contaminated clothing before reuse.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
First-aid measures after ingestion : Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell.

# VISCOSITY TUTELA Gear Oil SAE 85W-140

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : Inhalation of vapours may cause respiratory irritation.  
Symptoms/effects after skin contact : Prolonged or repeated contact may cause skin to become dry or cracked.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Dry powder. Foam. Carbon dioxide. Water fog.  
Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Burning produces irritating, toxic and noxious fumes.  
Explosion hazard : Product is not explosive.  
Reactivity : No dangerous reactions known.

### 5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses.  
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid all eye and skin contact and do not breathe vapour and mist. Always approach spills or fires from upwind/uphill.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Chemical goggles or safety glasses. Wear suitable protective clothing and gloves.  
Emergency procedures : Evacuate unnecessary personnel. Stop leak without risks if possible.

#### 6.1.2. For emergency responders

- Protective equipment : Chemical goggles or safety glasses. Wear suitable protective clothing and gloves.  
Emergency procedures : Stop leak if safe to do so. Ventilate area.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.  
Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container.

### 6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapour and mist.  
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container tightly closed.  
Incompatible products : Strong oxidizers.  
Prohibitions on mixed storage : Keep away from incompatible materials.  
Storage area : Store in dry, cool, well-ventilated area.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

# VISCOSITY TUTELA Gear Oil SAE 85W-140

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

**Long-chain alkyl amine (HMIRA Reg. No. 9939; Filing date 4/11/2016) (trade secret)**

Not applicable

### 8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Use rubber gloves.
Eye protection	: Chemical goggles or safety glasses.
Respiratory protection	: Where excessive vapour may result, wear approved mask. Appropriate dust or mist respirator should be used if airborne particles are generated when handling this material.
Other information	: Do not eat, drink or smoke when using this product.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: amber
Odour	: petroleum
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: -20 °C
Boiling point	: No data available
Flash point	: 210 °C
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 0.89 @ 15.5 °C
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 350 mm <sup>2</sup> /s @ 40 °C
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat. Incompatible materials.

### 10.5. Incompatible materials

Strong oxidizing agents.

# VISCOSITY TUTELA Gear Oil SAE 85W-140

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

### 10.6. Hazardous decomposition products

hydrocarbons. Carbon dioxide. Carbon monoxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Likely routes of exposure : Skin and eye contact; Inhalation

Acute toxicity : Not classified

Long-chain alkyl amine (HMIRA Reg. No. 9939; Filing date 4/11/2016) (trade secret)	
LD50 oral rat	612 mg/kg
LD50 dermal rat	251 mg/kg
LC50 Inhalation - Rat [ppm]	157 ppm/4h
ATE (oral)	612 mg/kg bodyweight
ATE (dermal)	251 mg/kg bodyweight
ATE (gases)	157 ppmv/4h
ATE (vapours)	0.5 mg/l/4h
ATE (dust,mist)	0.05 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified.  
(Long-chain alkyl amine not sensitizing <1.5%)

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Symptoms/effects after inhalation : Inhalation of vapours may cause respiratory irritation.

Symptoms/effects after skin contact : Prolonged or repeated contact may cause skin to become dry or cracked.

## SECTION 12: Ecological information

### 12.1. Toxicity

### 12.2. Persistence and degradability

VISCOSITY TUTELA Gear Oil SAE 85W-140	
Persistence and degradability	Not established.

### 12.3. Bioaccumulative potential

VISCOSITY TUTELA Gear Oil SAE 85W-140	
Bioaccumulative potential	Not established.

### 12.4. Mobility in soil

VISCOSITY TUTELA Gear Oil SAE 85W-140	
Ecology - soil	Not established.

### 12.5. Other adverse effects

Other information : No additional information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

# VISCOSITY TUTELA Gear Oil SAE 85W-140

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

### SECTION 14: Transport information

#### Department of Transportation (DOT)

In accordance with DOT

Not regulated.

#### Transportation of Dangerous Goods

Not regulated.

#### Transport by sea

Not regulated.

#### Air transport

Not regulated.

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

#### 15.2. International regulations

##### CANADA

**Long-chain alkyl amine (HMIRA Reg. No. 9939; Filing date 4/11/2016) (trade secret)**

Listed on the Canadian DSL (Domestic Substances List) inventory.

##### EU-Regulations

**Long-chain alkyl amine (HMIRA Reg. No. 9939; Filing date 4/11/2016) (trade secret)**

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

##### National regulations

**Long-chain alkyl amine (HMIRA Reg. No. 9939; Filing date 4/11/2016) (trade secret)**

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on Taiwan National Chemical Inventory

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

#### 15.3. US State regulations

**⚠ WARNING:** This product can expose you to Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Ethylene oxide(75-21-8)	X	X	X	X	2 µg/day	20 µg/day
Propylene oxide(75-56-9)	X					
1,4-dioxane(123-91-1)	X				30 µg/day	
Ethyl acrylate(140-88-5)	X					

# VISCOSITY TUTELA Gear Oil SAE 85W-140

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

### SECTION 16: Other information

Revision date : 12/04/2020

Data sources : ACGIH (American Conference of Government Industrial Hygienists). European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. NIOSH Occupational Health Guide for chemical Substances - Vol. II, September, 1978. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

Other information : None.

Full text of H-statements:

H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.


Abbreviations and acronyms:

	ACGIH (American Conference of Government Industrial Hygienists)
	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	OSHA: Occupational Safety & Health Administration
	TSCA: Toxic Substances Control Act
	STEL: Short Term Exposure Limits
	TWA: Time Weighted Average

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Indication of changes:

Product identifier.

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*