



VISCOSITY TUTELA Hydraulic Fluid 68

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Issue date: 09/17/2019

Revision date: 12/08/2020

Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : VISCOSITY TUTELA Hydraulic Fluid 68

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Lubricant
Restrictions on use : No data available

1.3. Details of the supplier of the safety data sheet

Supplier

Viscosity Oil Company
600 H Joliet Road
Willowbrook, IL 60527
T 630-850-4000 - F 630-850-4022

Importer

Viscosity Oil Company
1918 Boul.Saint-Regis
Dorval, QC H9P 1H6 - Canada

1.4. Emergency telephone number

Emergency number : (800) 424-9300
CHEMTREC (24 HOURS)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Not classified

2.2. Label elements

GHS US labelling

No labelling applicable

2.3. Other hazards

No data available

2.4. Unknown acute toxicity (GHS_US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

This mixture does not contain any substances to be mentioned according to the criteria of section 3.2 of HazCom 2012

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Gently wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse.
First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water.
First-aid measures after ingestion : Do NOT induce vomiting. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Inhalation of vapours may cause respiratory irritation.
Symptoms/effects after skin contact : Repeated or prolonged contact may cause skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

VISCOSITY TUTELA Hydraulic Fluid 68

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water fog. Foam. Carbon dioxide. Dry powder.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Burning produces irritating, toxic and noxious fumes.
Explosion hazard : Product is not explosive.
Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers.
Protection during firefighting : Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid all eye and skin contact and do not breathe vapour and mist.

6.1.1. For non-emergency personnel

Protective equipment : Wear suitable gloves.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear suitable gloves.
Emergency procedures : Stop leak if safe to do so. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Do not discharge into drains or the environment.

6.3. Methods and material for containment and cleaning up

For containment : Do not allow minor leaks or spills to accumulate on walking surfaces. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container.

6.4. Reference to other sections

Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapour and mist.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed.
Incompatible products : Strong oxidizers.
Incompatible materials : Heat sources.
Heat and ignition sources : Keep away from heat, sparks and flame.
Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

VISCOSITY TUTELA Hydraulic Fluid 68		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ oil mist
ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³ oil mist

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.

VISCOSITY TUTELA Hydraulic Fluid 68

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear suitable gloves.
Eye protection	: In case of splashing or aerosol production: protective goggles.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. NIOSH. Approved respirator.
Environmental exposure controls	: Prevent leakage or spillage. Prevent contaminated water run-off.
Other information	: Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: light amber
Odour	: petroleum
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: -30 °C
Boiling point	: No data available
Flash point	: 205 °C
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 0.863
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 68 mm ² /s @ 40 °C
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Extremely high or low temperatures.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

Burning produces irritating, toxic and noxious fumes. hydrocarbons. Carbon oxides (CO, CO₂). Nitrogen oxides. Phosphorus oxides. Sulphur oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure	: Inhalation; Skin and eye contact
---------------------------	------------------------------------

VISCOSITY TUTELA Hydraulic Fluid 68

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: Inhalation of vapours may cause respiratory irritation.
Symptoms/effects after skin contact	: Repeated or prolonged contact may cause skin irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No data available.

12.2. Persistence and degradability

VISCOSITY TUTELA Hydraulic Fluid 68	
Persistence and degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

VISCOSITY TUTELA Hydraulic Fluid 68	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

VISCOSITY TUTELA Hydraulic Fluid 68	
Ecology - soil	Not established.

12.5. Other adverse effects

Other information : No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated.

Transportation of Dangerous Goods

Not regulated.

Transport by sea

Not regulated.

Air transport

Not regulated.

VISCOSITY TUTELA Hydraulic Fluid 68

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

EU-Regulations

National regulations

15.3. US State regulations

⚠ WARNING: This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Toluene(108-88-3)		X				7000 µg/day
Ethyl acrylate(140-88-5)	X					
Benzene(71-43-2)	X	X	X		6.4 µg/day (oral); 13 µg/day (inhalation)	24 µg/day (oral); 49 µg/day (inhalation)

SECTION 16: Other information

Revision date : 12/08/2020

Data sources : ACGIH (American Conference of Government Industrial Hygienists). European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. NIOSH Occupational Health Guide for chemical Substances - Vol. II, September, 1978. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

Other information : None.


Abbreviations and acronyms:

	CAS (Chemical Abstracts Service) number
	CFR: Code of Federal Regulations
	CLP: Classification, Labelling, Packaging.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	OSHA: Occupational Safety & Health Administration
	TSCA: Toxic Substances Control Act

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Indication of changes:

Product identifier.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.