



# VISCOSITY TUTELA Transaxle Fluid SAE 80W-140

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Hazardous Products Regulations (SOR/2015-17) / Règlement sur les produits dangereux (DORS/2015-17)  
Issue date: 3/18/2020 Revision date: 8/19/2021 Supersedes: 12/8/2020 Version: 2.1

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Name : VISCOSITY TUTELA Transaxle Fluid SAE 80W-140

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Lubricants  
Restrictions on use : No additional information available

#### 1.3. Supplier

##### Supplier

Viscosity Oil Company  
600 H Joliet Road  
Willowbrook, IL 60527  
T 630-850-4000 - F 630-850-4022

##### Importer

Viscosity Oil Company  
1918 Boul.Saint-Regis  
Dorval, QC H9P 1H6 - Canada

#### 1.4. Emergency telephone number

Emergency number : (800) 424-9300  
CHEMTREC (24 HOURS)

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS classification

Not classified

#### 2.2. GHS Label elements, including precautionary statements

##### GHS labeling

No labeling applicable

#### 2.3. Other hazards which do not result in classification

No additional information available

#### 2.4. Unknown acute toxicity (GHS)

- 0.1% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
- 0.1% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
- 0.1% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	% (w/w)	GHS classification
Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (KV > 20.5 cSt)	CAS-No.: 64742-54-7	60 - 100	Not classified
Zinc alkyl dithiophosphate	CAS-No.: 68649-42-3	<1.5	Eye Dam. 1, H318 Aquatic Chronic 2, H411

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

# VISCOSITY TUTELA Transaxle Fluid SAE 80W-140

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Hazardous Products Regulations (SOR/2015-17) / Règlement sur les produits dangereux (DORS/2015-17)

- First-aid measures after skin contact : Wash skin thoroughly with mild soap and water. Take off contaminated clothing and wash it before reuse.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Get medical advice/attention.

### 4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after inhalation : May cause irritation of the mucous membranes.
- Symptoms/effects after skin contact : Repeated or prolonged contact may cause skin irritation.
- Symptoms/effects after ingestion : May cause a light irritation of the linings of the mouth, throat, and gastrointestinal tract.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry chemical. Foam. Water fog.
- Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

- Fire hazard : Burning produces irritating, toxic and noxious fumes.
- Explosion hazard : Product is not explosive.

### 5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Cool adjacent structures and containers with water spray to protect and prevent ignition. Do not allow run-off from fire fighting to enter drains or water courses.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid all eye and skin contact and do not breathe vapor and mist.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Chemical goggles or safety glasses. Wear suitable gloves.
- Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

- Protective equipment : Chemical goggles or safety glasses. Wear suitable gloves.
- Emergency procedures : Ventilate area. Stop leak if safe to do so.

### 6.2. Environmental precautions

Prevent dispersion.

### 6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Take up in non-combustible absorbent material and shove into container for disposal.

### 6.4. Reference to other sections

Section 7: safe handling. Section 8: personal protective equipment.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist.
- Hygiene measures : Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container closed when not in use.
- Incompatible products : Strong oxidizers.

# VISCOSITY TUTELA Transaxle Fluid SAE 80W-140

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Hazardous Products Regulations (SOR/2015-17) / Règlement sur les produits dangereux (DORS/2015-17)

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

VISCOSITY TUTELA Transaxle Fluid SAE 80W-140	
No additional information available	
Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (KV > 20.5 cSt) (64742-54-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Oil mist
ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
ACGIH STEL (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
USA - OSHA - Occupational Exposure Limits	
Local name	Oil mist
OSHA PEL (TWA) [1]	5 mg/m <sup>3</sup>
Zinc alkyl dithiophosphate (68649-42-3)	
No additional information available	

#### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Avoid creating mist or spray. Avoid splashing.  
Environmental exposure controls : Prevent leakage or spillage.

#### 8.3. Individual protection measures/Personal protective equipment

##### Personal protective equipment:

Avoid all unnecessary exposure.

<b>Hand protection:</b>
Wear suitable gloves. nitrile rubber gloves
<b>Eye protection:</b>
In case of splashing or aerosol production: protective goggles.
<b>Respiratory protection:</b>
In case of inadequate ventilation wear respiratory protection. Wear appropriate mask

##### Other information:

Do not eat, drink or smoke when using this product.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: amber
Odor	: petroleum
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: ~ 240 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available

# VISCOSITY TUTELA Transaxle Fluid SAE 80W-140

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Hazardous Products Regulations (SOR/2015-17) / Règlement sur les produits dangereux (DORS/2015-17)

Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 280 mm <sup>2</sup> /s @ 40 °C
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

VOC content : 0 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

Strong oxidizers.

### 10.6. Hazardous decomposition products

Burning produces irritating, toxic and noxious fumes. Carbon oxides (CO, CO<sub>2</sub>). hydrocarbons. Phosphorus oxides. Nitrogen oxides. Sulfur oxides.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

VISCOSITY TUTELA Transaxle Fluid SAE 80W-140	
Unknown acute toxicity (GHS)	0.1% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 0.1% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 0.1% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (KV > 20.5 cSt) (64742-54-7)	
LD50 Oral rat	> 5000 mg/kg
LD50 Dermal rabbit	> 2000 mg/kg
LC50 Inhalation rat	> 5.53 mg/l/4h
ATE (dust, mist)	5.55 mg/l/4h

Zinc alkyl dithiophosphate (68649-42-3)	
LD50 Oral rat	3100 mg/kg
LD50 Dermal rabbit	> 5000 mg/kg
ATE (oral)	3100 mg/kg body weight

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified. (Zinc alkyl dithiophosphate not irritating <10%.)
Respiratory or skin sensitization	: Not classified

# VISCOSITY TUTELA Transaxle Fluid SAE 80W-140

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Hazardous Products Regulations (SOR/2015-17) / Règlement sur les produits dangereux (DORS/2015-17)

Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: 280 mm <sup>2</sup> /s @ 40 °C
Likely routes of exposure	: Skin and eye contact. Inhalation.
Symptoms/effects after inhalation	: May cause irritation of the mucous membranes.
Symptoms/effects after skin contact	: Repeated or prolonged contact may cause skin irritation.
Symptoms/effects after ingestion	: May cause a light irritation of the linings of the mouth, throat, and gastrointestinal tract.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>Distillates (petroleum), hydrotreated heavy paraffinic (DMSO &lt; 3%) (KV &gt; 20.5 cSt) (64742-54-7)</b>	
EC50 crustacea	> 10000 mg/l
<b>Zinc alkyl dithiophosphate (68649-42-3)</b>	
LC50 fish 1	4.4 mg/l 96 h oncorhynchus mykiss
EC50 crustacea	1.2 mg/l 48 h

### 12.2. Persistence and degradability

<b>VISCOSITY TUTELA Transaxle Fluid SAE 80W-140</b>	
Persistence and degradability	Not established.

### 12.3. Bioaccumulative potential

<b>VISCOSITY TUTELA Transaxle Fluid SAE 80W-140</b>	
Bioaccumulative potential	Not established.

### 12.4. Mobility in soil

<b>VISCOSITY TUTELA Transaxle Fluid SAE 80W-140</b>	
Ecology - soil	Not established.

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Recycle product or dispose safely.
Ecology - waste materials	: Avoid release to the environment.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Not regulated.

### Transportation of Dangerous Goods

Not regulated.

# VISCOSITY TUTELA Transaxle Fluid SAE 80W-140

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Hazardous Products Regulations (SOR/2015-17) / Règlement sur les produits dangereux (DORS/2015-17)

### Transport by sea

Not regulated.

### Air transport

Not regulated.

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are listed as Active, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

### 15.2. International regulations

#### CANADA

##### **Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (KV > 20.5 cSt) (64742-54-7)**

Listed on the Canadian DSL (Domestic Substances List)

##### **Zinc alkyl dithiophosphate (68649-42-3)**

Listed on the Canadian DSL (Domestic Substances List)

#### EU-Regulations

##### **Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (KV > 20.5 cSt) (64742-54-7)**

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

##### **Zinc alkyl dithiophosphate (68649-42-3)**

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

#### National regulations

##### **Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (KV > 20.5 cSt) (64742-54-7)**

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on Taiwan National Chemical Inventory  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

# VISCOSITY TUTELA Transaxle Fluid SAE 80W-140

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Hazardous Products Regulations (SOR/2015-17) / Règlement sur les produits dangereux (DORS/2015-17)

### Zinc alkyl dithiophosphate (68649-42-3)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on Taiwan National Chemical Inventory  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Not listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

### 15.3. US State regulations

**⚠ WARNING:** This product can expose you to ethylbenzene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
ethylbenzene(100-41-4)	X				54 µg/day (inhalation); 41 µg/day (oral)	
Naphthalene(91-20-3)	X				5.8 µg/day	
cumene(98-82-8)	X					

### SECTION 16: Other information

Revision date : 08/19/2021  
Data sources : ACGIH (American Conference of Government Industrial Hygienists). Canadian Centre for Occupational Health and Safety. Accessed at: [http://www.ccohs.ca/oshanswers/legisl/whmis\\_classifi.html](http://www.ccohs.ca/oshanswers/legisl/whmis_classifi.html). European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.  
Other information : None.

### Full text of H-phrases

H318	Causes serious eye damage
H411	Toxic to aquatic life with long lasting effects

### Abbreviations and acronyms

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CFR: Code of Federal Regulations
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population


# VISCOSITY TUTELA Transaxle Fluid SAE 80W-140

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Hazardous Products Regulations (SOR/2015-17) / Règlement sur les produits dangereux (DORS/2015-17)

Abbreviations and acronyms	
	OSHA: Occupational Safety & Health Administration
	TSCA: Toxic Substances Control Act
	TWA: Time Weighted Average
	STEL: Short Term Exposure Limits

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.  
NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.  
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Indication of changes:			
Section	Changed item	Change	Comments
3	Composition/Information on ingredients	Added	
8	Occupational Exposure Limits	Added	Oil mist

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.