



VISCOSITY TUTELA Transaxle Fluid SAE 80W-140

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR
Issue date: 03/18/2020 Revision date: 12/08/2020 Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : VISCOSITY TUTELA Transaxle Fluid SAE 80W-140

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Lubricant
Restrictions on use : No data available

1.3. Details of the supplier of the safety data sheet

Supplier

Viscosity Oil Company
600 H Joliet Road
Willowbrook, IL 60527
T 630-850-4000 - F 630-850-4022

Importer

Viscosity Oil Company
1918 Boul.Saint-Regis
Dorval, QC H9P 1H6 - Canada

1.4. Emergency telephone number

Emergency number : (800) 424-9300
CHEMTREC (24 HOURS)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Not classified

2.2. Label elements

GHS US labelling

No labelling applicable

2.3. Other hazards

No data available

2.4. Unknown acute toxicity (GHS_US)

0.1% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
0.1% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
0.1% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	% (w/w)	GHS US classification
Zinc alkyl dithiophosphate	(CAS-No.) 68649-42-3	<1.5	Eye Dam. 1, H318 Aquatic Chronic 2, H411

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin thoroughly with mild soap and water. Take off contaminated clothing and wash it before reuse.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Get medical advice/attention.

VISCOSITY TUTELA Transaxle Fluid SAE 80W-140

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : May cause irritation of the mucous membranes.
Symptoms/effects after skin contact : Repeated or prolonged contact may cause skin irritation.
Symptoms/effects after ingestion : May cause a light irritation of the linings of the mouth, throat, and gastrointestinal tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry chemical. Foam. Water fog.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Burning produces irritating, toxic and noxious fumes.
Explosion hazard : Product is not explosive.
Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

- Firefighting instructions : Cool adjacent structures and containers with water spray to protect and prevent ignition. Do not allow run-off from fire fighting to enter drains or water courses.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid all eye and skin contact and do not breathe vapour and mist.

6.1.1. For non-emergency personnel

- Protective equipment : Chemical goggles or safety glasses. Wear suitable gloves.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Chemical goggles or safety glasses. Wear suitable gloves.
Emergency procedures : Ventilate area. Stop leak if safe to do so.

6.2. Environmental precautions

Prevent dispersion.

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : Take up in non-combustible absorbent material and shove into container for disposal.

6.4. Reference to other sections

Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapour and mist.
Hygiene measures : Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container closed when not in use.
Incompatible products : Strong oxidizers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

VISCOSITY TUTELA Transaxle Fluid SAE 80W-140		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ Refined mineral oil, mist
ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³ Refined mineral oil, mist

VISCOSITY TUTELA Transaxle Fluid SAE 80W-140

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Zinc alkyl dithiophosphate (68649-42-3)

Not applicable

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Avoid creating mist or spray. Avoid splashing.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear suitable gloves. nitrile rubber gloves.
Eye protection	: In case of splashing or aerosol production: protective goggles.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. Wear appropriate mask.
Environmental exposure controls	: Prevent leakage or spillage.
Other information	: Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: amber
Odour	: petroleum
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: ~ 240 °C
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 280 mm ² /s @ 40 °C
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

VOC content	: 0 %
-------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong oxidizers.

VISCOSITY TUTELA Transaxle Fluid SAE 80W-140

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

10.6. Hazardous decomposition products

Burning produces irritating, toxic and noxious fumes. Carbon oxides (CO, CO₂). hydrocarbons. Phosphorus oxides. Nitrogen oxides. Sulphur oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Skin and eye contact; Inhalation

Acute toxicity : Not classified

Zinc alkyl dithiophosphate (68649-42-3)	
LD50 oral rat	3100 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
ATE (oral)	3100 mg/kg bodyweight

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified.
(Zinc alkyl dithiophosphate not irritating <10%.)

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Symptoms/effects after inhalation : May cause irritation of the mucous membranes.

Symptoms/effects after skin contact : Repeated or prolonged contact may cause skin irritation.

Symptoms/effects after ingestion : May cause a light irritation of the linings of the mouth, throat, and gastrointestinal tract.

SECTION 12: Ecological information

12.1. Toxicity

Zinc alkyl dithiophosphate (68649-42-3)	
LC50 fish 1	4.4 mg/l 96 h oncorhynchus mykiss
EC50 crustacea	1.2 mg/l 48 h

12.2. Persistence and degradability

VISCOSITY TUTELA Transaxle Fluid SAE 80W-140	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

VISCOSITY TUTELA Transaxle Fluid SAE 80W-140	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

VISCOSITY TUTELA Transaxle Fluid SAE 80W-140	
Ecology - soil	Not established.

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Recycle product or dispose safely.

Ecology - waste materials : Avoid release to the environment.

VISCOSITY TUTELA Transaxle Fluid SAE 80W-140

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated.

Transportation of Dangerous Goods

Not regulated.

Transport by sea

Not regulated.

Air transport

Not regulated.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

Zinc alkyl dithiophosphate (68649-42-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

Zinc alkyl dithiophosphate (68649-42-3)


Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Zinc alkyl dithiophosphate (68649-42-3)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on Taiwan National Chemical Inventory
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Not listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

15.3. US State regulations

 **WARNING:** This product can expose you to ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
ethylbenzene(100-41-4)	X				54 µg/day (inhalation); 41 µg/day (oral)	
Naphthalene(91-20-3)	X				5.8 µg/day	
cumene(98-82-8)	X					

VISCOSITY TUTELA Transaxle Fluid SAE 80W-140

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

SECTION 16: Other information

Revision date : 12/08/2020

Data sources : ACGIH (American Conference of Government Industrial Hygienists). Canadian Centre for Occupational Health and Safety. Accessed at: http://www.ccohs.ca/oshanswers/legisl/whmis_classifi.html. European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

Other information : None.

Full text of H-statements:

H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.


Abbreviations and acronyms:

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CFR: Code of Federal Regulations
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	OSHA: Occupational Safety & Health Administration
	TSCA: Toxic Substances Control Act
	TWA: Time Weighted Average
	STEL: Short Term Exposure Limits

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Indication of changes:

Product identifier.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.