



VISCOSITY ULTRACTION Original THF SS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Issue date: 08/26/2020

Revision date: 12/08/2020

Supersedes: 09/15/2020

Version: 3.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : VISCOSITY ULTRACTION Original THF SS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Lubricant
Restrictions on use : No data available

1.3. Details of the supplier of the safety data sheet

Supplier

Viscosity Oil Company
600 H Joliet Road
Willowbrook, IL 60527
T 630-850-4000 - F 630-850-4022

Importer

Viscosity Oil Company
1918 Boul.Saint-Regis
Dorval, QC H9P 1H6 - Canada

1.4. Emergency telephone number

Emergency number : (800) 424-9300
CHEMTREC (24 HOURS)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin sensitisation, Category 1 H317
Full text of H statements : see section 16

2.2. Label elements

GHS US labelling

Hazard pictograms (GHS) :



GHS07

Signal word (GHS) : Warning
Hazard statements (GHS_US) : H317 - May cause an allergic skin reaction.
Precautionary statements (GHS) : P261 - Avoid breathing mist, spray, vapours.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P280 - Wear protective gloves, protective clothing.
P302+P352 - If on skin: Wash with plenty of water.
P321 - Specific treatment (see First aid measures on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P363 - Wash contaminated clothing before reuse.
P501 - Dispose of contents/container to Collection point.

2.3. Other hazards

No data available

2.4. Unknown acute toxicity (GHS_US)

1.58% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
1.58% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
1.58% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	% (w/w)	GHS US classification
Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%)	(CAS.No.) 64742-54-7	0 - 25	Asp. Tox. 1, H304

VISCOSITY ULTRACTION Original THF SS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Name	Product identifier	% (w/w)	GHS US classification
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%)	(CAS-No.) 72623-87-1	0 - 25	Asp. Tox. 1, H304
Benzenesulfonic acid, propenated, calcium salt, overbased	(CAS-No.) 68610-84-4	0.5 - 1.5	Skin Sens. 1, H317 Aquatic Chronic 4, H413

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If medical advice is needed, have product container or label at hand.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin thoroughly with mild soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : Inhalation may cause: irritation, coughing, shortness of breath.
- Symptoms/effects after skin contact : May cause an allergic skin reaction. Repeated or prolonged skin contact may cause dermatitis and defatting.

4.3. Indication of any immediate medical attention and special treatment needed

All treatments should be based on observed signs and symptoms of distress in the patient.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Dry chemical. Carbon dioxide. Foam.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : No specific fire or explosion hazard.
- Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

- Firefighting instructions : Cool adjacent structures and containers with water spray to protect and prevent ignition. Do not allow run-off from fire fighting to enter drains or water courses.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Use self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Do not breathe aerosol. Do not breathe vapour. Do not get in eyes, on skin, or on clothing.

6.1.1. For non-emergency personnel

- Protective equipment : Refer to section 8.2.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Refer to section 8.2.
- Emergency procedures : Ventilate area. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Take up in non-combustible absorbent material and shove into container for disposal.

6.4. Reference to other sections

Section 7: safe handling. Section 8: personal protective equipment.

VISCOSITY ULTRACTION Original THF SS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Do not get in eyes, on skin, or on clothing. Do not breathe vapours. Do not breathe aerosol.
- Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Always wash your hands immediately after handling this product, and once again before leaving the workplace.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container closed when not in use.
- Incompatible products : Strong oxidizers.
- Heat and ignition sources : Keep away from heat, sparks and flame.
- Prohibitions on mixed storage : Incompatible materials.
- Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³
OSHA	OSHA PEL TWA [1]	5 mg/m ³
Benzenesulfonic acid, propenated, calcium salt, overbased (68610-84-4)		
Not applicable		
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%) (72623-87-1)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ oil mist

8.2. Exposure controls

- Appropriate engineering controls : Avoid splashing. Provide local exhaust ventilation of closed transfer systems to minimize exposures.
- Personal protective equipment : Avoid all unnecessary exposure.
- Hand protection : Wear suitable gloves. nitrile rubber gloves.
- Eye protection : In case of splashing or aerosol production: protective goggles.
- Skin and body protection : Long sleeved protective clothing.
- Respiratory protection : In case of inadequate ventilation wear respiratory protection. Wear appropriate mask.
- Other information : Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Colour : dark brown
- Odour : petroleum
- Odour threshold : No data available
- pH : No data available
- Melting point : No data available
- Freezing point : No data available
- Boiling point : No data available
- Flash point : > 200 °C
- Relative evaporation rate (butylacetate=1) : No data available
- Flammability (solid, gas) : No data available
- Vapour pressure : No data available
- Relative vapour density at 20 °C : No data available
- Relative density : No data available
- Solubility : No data available

VISCOSITY ULTRACTION Original THF SS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 60 mm ² /s @ 40 °C
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

Thermal decomposition generates : Carbon oxides (CO, CO₂). Nitrogen oxides. Phosphorus oxides. hydrocarbons. Sulphur oxides. Burning produces irritating, toxic and noxious fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Skin and eye contact; Inhalation

Acute toxicity : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 5.53 mg/l/4h
Benzenesulfonic acid, propenated, calcium salt, overbased (68610-84-4)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg bodyweight
LC50 Inhalation - Rat	> 1.9 mg/l/4h read-across Sulfonic acids, petroleum, calcium salts, overbased
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%) (72623-87-1)	
LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rabbit	> 2000 mg/kg bodyweight

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

VISCOSITY ULTRACTION Original THF SS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Symptoms/effects after inhalation	: Inhalation may cause: irritation, coughing, shortness of breath.
Symptoms/effects after skin contact	: May cause an allergic skin reaction. Repeated or prolonged skin contact may cause dermatitis and defatting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Harmful to aquatic life with long lasting effects.

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)	
EC50 crustacea	> 10000 mg/l

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%) (72623-87-1)	
LC50 fish 1	> 100 mg/l
EC50 crustacea	> 10000 mg/l
ErC50 algae	≥ 100 mg/l
NOEC (acute)	> 100 mg/kg

12.2. Persistence and degradability

VISCOSITY ULTRACTION Original THF SS	
Persistence and degradability	May cause long-term adverse effects in the environment.

Benzenesulfonic acid, propenated, calcium salt, overbased (68610-84-4)	
Persistence and degradability	Not readily biodegradable.

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%) (72623-87-1)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	2 – 4 %

12.3. Bioaccumulative potential

VISCOSITY ULTRACTION Original THF SS	
Bioaccumulative potential	Not established.

Benzenesulfonic acid, propenated, calcium salt, overbased (68610-84-4)	
BCF fish 1	0.001 mg/l
BCF fish 2	0.01 mg/l
Log Kow	5.7 – 5.8

12.4. Mobility in soil

VISCOSITY ULTRACTION Original THF SS	
Ecology - soil	Not established.

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%) (72623-87-1)	
Mobility in soil	22 %

12.5. Other adverse effects

Other information : No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated.

Transportation of Dangerous Goods

Not regulated.

VISCOSITY ULTRACTION Original THF SS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Transport by sea

Not regulated.

Air transport

Not regulated.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Benzenesulfonic acid, propenated, calcium salt, overbased (68610-84-4)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%) (72623-87-1)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Benzenesulfonic acid, propenated, calcium salt, overbased (68610-84-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

VISCOSITY ULTRACTION Original THF SS

All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the TCSI (Taiwan Chemical Substance Inventory)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Benzenesulfonic acid, propenated, calcium salt, overbased (68610-84-4)

Listed on the Inventory of Existing Chemical Substances Produced or Imported in China (IECSC).
Not listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on Taiwan National Chemical Inventory
Not listed on Phillipines Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%) (72623-87-1)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on Taiwan National Chemical Inventory
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

15.3. US State regulations

⚠ WARNING: This product can expose you to ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

VISCOSITY ULTRACTION Original THF SS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
ethylbenzene(100-41-4)	X				54 µg/day (inhalation); 41 µg/day (oral)	
Naphthalene(91-20-3)	X				5.8 µg/day	
cumene(98-82-8)	X					

SECTION 16: Other information

Revision date : 12/08/2020

Data sources : ACGIH (American Conference of Government Industrial Hygienists). Canadian Centre for Occupational Health and Safety. Accessed at: http://www.ccohs.ca/oshanswers/legisl/whmis_classifi.html. European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

Other information : None.

Full text of H-statements:

H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H413	May cause long lasting harmful effects to aquatic life.


Abbreviations and acronyms:

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CFR: Code of Federal Regulations
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	OSHA: Occupational Safety & Health Administration
	TSCA: Toxic Substances Control Act
	TWA: Time Weighted Average
	STEL: Short Term Exposure Limits

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Indication of changes:
Product identifier.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.