



VISCOSITY UNITEK 3000K Diesel Engine Oil SS SAE 10W-40 CK-4

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Issue date: 08/08/2019

Revision date: 12/04/2020

Supersedes: 09/24/2019

Version: 3.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : VISCOSITY UNITEK 3000K Diesel Engine Oil SS SAE 10W-40 CK-4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Lubricant
Restrictions on use : No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Viscosity Oil Company
600 H Joliet Road
Willowbrook, IL 60527
T 630-850-4000 - F 630-850-4022

Other

Viscosity Oil Company
1918 Boul.Saint-Regis
Dorval, QC H9P 1H6 - Canada

1.4. Emergency telephone number

Emergency number : (800) 424-9300
CHEMTREC (24 HOURS)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Not classified

2.2. Label elements

GHS-US labelling

No labelling applicable

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS_US)

5.99% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
5.99% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
5.99% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	% (w/w)	GHS classification
Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%)	(CAS-No.) 64742-54-7	40 - 50	Asp. Tox. 1, H304
Zinc alkyl dithiophosphate	(CAS-No.) 113706-15-3	0.5 - 1.5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin thoroughly with mild soap and water. Wash contaminated clothing before reuse.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

VISCOSITY UNITEK 3000K Diesel Engine Oil SS SAE 10W-40 CK-4

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

First-aid measures after ingestion : Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Inhalation of vapours may cause respiratory irritation.

Symptoms/effects after skin contact : Prolonged or repeated contact may cause skin to become dry or cracked.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry powder. Foam. Carbon dioxide. Water fog.

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Burning produces irritating, toxic and noxious fumes.

Explosion hazard : Product is not explosive.

Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid all eye and skin contact and do not breathe vapour and mist. Always approach spills or fires from upwind/uphill.

6.1.1. For non-emergency personnel

Protective equipment : Chemical goggles or safety glasses. Wear suitable protective clothing and gloves.

Emergency procedures : Evacuate unnecessary personnel. Stop leak without risks if possible.

6.1.2. For emergency responders

Protective equipment : Chemical goggles or safety glasses. Wear suitable protective clothing and gloves.

Emergency procedures : Stop leak if safe to do so. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container.

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapour and mist.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed.

Incompatible products : Strong oxidizers.

Prohibitions on mixed storage : Keep away from incompatible materials.

Storage area : Store in dry, cool, well-ventilated area.

VISCOSITY UNITEK 3000K Diesel Engine Oil SS SAE 10W-40 CK-4

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³
OSHA	OSHA PEL TWA [1]	5 mg/m ³

Zinc alkyl dithiophosphate (113706-15-3)	
Not applicable	

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Use rubber gloves.
Eye protection	: Chemical goggles or safety glasses.
Respiratory protection	: Where excessive vapour may result, wear approved mask. Appropriate dust or mist respirator should be used if airborne particles are generated when handling this material.
Other information	: Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: amber
Odour	: petroleum
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 215 °C
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 0.868 @ 15.5 °C
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 110 mm ² /s @ 40 °C
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

VISCOSITY UNITEK 3000K Diesel Engine Oil SS SAE 10W-40 CK-4

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat. Incompatible materials.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

hydrocarbons. Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Skin and eye contact; Inhalation

Acute toxicity : Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 5.53 mg/l/4h

Zinc alkyl dithiophosphate (113706-15-3)	
LD50 oral rat	2600 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
ATE (oral)	2600 mg/kg bodyweight

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified.

(Zinc alkyl dithiophosphate not irritating <10%.)

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Symptoms/effects after inhalation : Inhalation of vapours may cause respiratory irritation.

Symptoms/effects after skin contact : Prolonged or repeated contact may cause skin to become dry or cracked.

SECTION 12: Ecological information

12.1. Toxicity

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)	
EC50 crustacea	> 10000 mg/l

Zinc alkyl dithiophosphate (113706-15-3)	
LC50 fish 1	4.5 mg/l 96 h Rainbow trout

12.2. Persistence and degradability

VISCOSITY UNITEK 3000K Diesel Engine Oil SS SAE 10W-40 CK-4	
Persistence and degradability	Not established.

Zinc alkyl dithiophosphate (113706-15-3)	
Persistence and degradability	Not readily biodegradable.

12.3. Bioaccumulative potential

VISCOSITY UNITEK 3000K Diesel Engine Oil SS SAE 10W-40 CK-4	
Bioaccumulative potential	Not established.

VISCOSITY UNITEK 3000K Diesel Engine Oil SS SAE 10W-40 CK-4

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Zinc alkyl dithiophosphate (113706-15-3)	
Log Pow	0.9

12.4. Mobility in soil

VISCOSITY UNITEK 3000K Diesel Engine Oil SS SAE 10W-40 CK-4	
Ecology - soil	Not established.

Zinc alkyl dithiophosphate (113706-15-3)	
Ecology - soil	Absorbs to soil particles and will not be mobile.

12.5. Other adverse effects

Other information : No additional information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated.

Transportation of Dangerous Goods

Not regulated.

Transport by sea

Not regulated.

Air transport

Not regulated.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S

Alkyl esters	CAS-No. 68610-90-2	1 - 5%
--------------	--------------------	--------

Zinc alkyl dithiophosphate (113706-15-3)	
EPA TSCA Regulatory Flag	P - P - indicates a commenced Premanufacture Notice (PMN) substance.

15.2. International regulations

CANADA

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	

Zinc alkyl dithiophosphate (113706-15-3)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	

EU-Regulations

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

Zinc alkyl dithiophosphate (113706-15-3)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

VISCOSITY UNITEK 3000K Diesel Engine Oil SS SAE 10W-40 CK-4

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

National regulations

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the TCSI (Taiwan Chemical Substance Inventory)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

15.3. US State regulations

⚠ WARNING: This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Benzene(71-43-2)	X	X	X		6.4 µg/day (oral); 13 µg/day (inhalation)	24 µg/day (oral); 49 µg/day (inhalation)
Toluene(108-88-3)		X				7000 µg/day
lead/lead compounds()	X	X	X	X	15 µg/day	0.5 µg/day
Nickel compounds(trade secret)	X					

SECTION 16: Other information

Revision date : 12/04/2020
Data sources : ACGIH (American Conference of Government Industrial Hygienists). European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. NIOSH Occupational Health Guide for chemical Substances - Vol. II, September, 1978. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.
Other information : None.

Full text of H-statements:

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:


	ACGIH (American Conference of Government Industrial Hygienists)
	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	OSHA: Occupational Safety & Health Administration
	TSCA: Toxic Substances Control Act
	STEL: Short Term Exposure Limits
	TWA: Time Weighted Average

VISCOSITY UNITEK 3000K Diesel Engine Oil SS SAE 10W-40 CK-4

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

NFPA health hazard	: 1 - Materials that, under emergency conditions, can cause significant irritation.
NFPA fire hazard	: 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Indication of changes:
Product identifier.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.