



VISCOSITY UNITEK 3000LS Diesel Engine Oil SAE 15W-40 CK-4

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR
Issue date: 08/08/2019 Revision date: 12/03/2020 Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : VISCOSITY UNITEK 3000LS Diesel Engine Oil SAE 15W-40 CK-4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Lubricant
Restrictions on use : No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Viscosity Oil Company
600 H Joliet Road
Willowbrook, IL 60527
T 630-850-4000 - F 630-850-4022

Importer

Viscosity Oil Company
1918 Boul.Saint-Regis
Dorval, QC H9P 1H6 - Canada

1.4. Emergency telephone number

Emergency number : (800) 424-9300
CHEMTREC (24 HOURS)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Not classified

2.2. Label elements

GHS labelling

No labelling applicable

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS)

5.58% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
5.58% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
5.58% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % (w/w) | GHS classification |
|----------------------------|-----------------------|-----------|--|
| Zinc alkyl dithiophosphate | (CAS-No.) 113706-15-3 | 0.5 - 1.5 | Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411 |

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin thoroughly with mild soap and water. Wash contaminated clothing before reuse.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
First-aid measures after ingestion : Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : Inhalation of vapours may cause respiratory irritation.

VISCOSITY UNITEK 3000LS Diesel Engine Oil SAE 15W-40 CK-4

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Symptoms/effects after skin contact : Prolonged or repeated contact may cause skin to become dry or cracked.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry powder. Foam. Carbon dioxide. Water fog.

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Burning produces irritating, toxic and noxious fumes.

Explosion hazard : Product is not explosive.

Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid all eye and skin contact and do not breathe vapour and mist. Always approach spills or fires from upwind/uphill.

6.1.1. For non-emergency personnel

Protective equipment : Chemical goggles or safety glasses. Wear suitable protective clothing and gloves.

Emergency procedures : Evacuate unnecessary personnel. Stop leak without risks if possible.

6.1.2. For emergency responders

Protective equipment : Chemical goggles or safety glasses. Wear suitable protective clothing and gloves.

Emergency procedures : Stop leak if safe to do so. Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Absorb and/or contain spill with inert material, then place in suitable container.

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapour and mist.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed.

Incompatible products : Strong oxidizers.

Prohibitions on mixed storage : Keep away from incompatible materials.

Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Zinc alkyl dithiophosphate (113706-15-3)

Not applicable

VISCOSITY UNITEK 3000LS Diesel Engine Oil SAE 15W-40 CK-4

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

8.2. Exposure controls

| | |
|----------------------------------|--|
| Appropriate engineering controls | : Ensure good ventilation of the work station. |
| Personal protective equipment | : Avoid all unnecessary exposure. |
| Hand protection | : Use rubber gloves. |
| Eye protection | : Chemical goggles or safety glasses. |
| Respiratory protection | : Where excessive vapour may result, wear approved mask. Appropriate dust or mist respirator should be used if airborne particles are generated when handling this material. |
| Other information | : Do not eat, drink or smoke when using this product. |

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|----------------------------------|
| Physical state | : Liquid |
| Colour | : amber |
| Odour | : petroleum |
| Odour threshold | : No data available |
| pH | : No data available |
| Melting point | : No data available |
| Freezing point | : -30 °C |
| Boiling point | : No data available |
| Flash point | : 220 °C |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapour pressure | : No data available |
| Relative vapour density at 20 °C | : No data available |
| Relative density | : 0.873 @ 15.5 °C |
| Solubility | : No data available |
| Log Pow | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity, kinematic | : 120 mm ² /s @ 40 °C |
| Viscosity, dynamic | : No data available |
| Explosive limits | : No data available |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat. Incompatible materials.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

hydrocarbons. Carbon dioxide. Carbon monoxide.

VISCOSITY UNITEK 3000LS Diesel Engine Oil SAE 15W-40 CK-4

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Skin and eye contact; Inhalation

Acute toxicity : Not classified

| Zinc alkyl dithiophosphate (113706-15-3) | |
|--|-----------------------|
| LD50 oral rat | 2600 mg/kg |
| LD50 dermal rabbit | > 3160 mg/kg |
| ATE (oral) | 2600 mg/kg bodyweight |

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified.

(Zinc alkyl dithiophosphate not irritating <10%.)

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Symptoms/effects after inhalation : Inhalation of vapours may cause respiratory irritation.

Symptoms/effects after skin contact : Prolonged or repeated contact may cause skin to become dry or cracked.

SECTION 12: Ecological information

12.1. Toxicity

| Zinc alkyl dithiophosphate (113706-15-3) | |
|--|-----------------------------|
| LC50 fish 1 | 4.5 mg/l 96 h Rainbow trout |

12.2. Persistence and degradability

| VISCOSITY UNITEK 3000LS Diesel Engine Oil SAE 15W-40 CK-4 | |
|---|------------------|
| Persistence and degradability | Not established. |

| Zinc alkyl dithiophosphate (113706-15-3) | |
|--|----------------------------|
| Persistence and degradability | Not readily biodegradable. |

12.3. Bioaccumulative potential

| VISCOSITY UNITEK 3000LS Diesel Engine Oil SAE 15W-40 CK-4 | |
|---|------------------|
| Bioaccumulative potential | Not established. |

| Zinc alkyl dithiophosphate (113706-15-3) | |
|--|-----|
| Log Pow | 0.9 |

12.4. Mobility in soil

| VISCOSITY UNITEK 3000LS Diesel Engine Oil SAE 15W-40 CK-4 | |
|---|------------------|
| Ecology - soil | Not established. |

| Zinc alkyl dithiophosphate (113706-15-3) | |
|--|---|
| Ecology - soil | Absorbs to soil particles and will not be mobile. |

12.5. Other adverse effects

Other information : No additional information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

VISCOSITY UNITEK 3000LS Diesel Engine Oil SAE 15W-40 CK-4

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated.

Transportation of Dangerous Goods

Not regulated.

Transport by sea

Not regulated.

Air transport

Not regulated.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S

| | | |
|--------------|--------------------|--------|
| Alkyl esters | CAS-No. 68610-90-2 | 1 – 5% |
|--------------|--------------------|--------|

Zinc alkyl dithiophosphate (113706-15-3)

EPA TSCA Regulatory Flag P - P - indicates a commenced Premanufacture Notice (PMN) substance.

15.2. International regulations

CANADA

Zinc alkyl dithiophosphate (113706-15-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

Zinc alkyl dithiophosphate (113706-15-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

15.3. US State regulations

WARNING: This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

| Component | Carcinogenicity | Developmental toxicity | Reproductive toxicity male | Reproductive toxicity female | No significant risk level (NSRL) | Maximum allowable dose level (MADL) |
|--------------------------------|-----------------|------------------------|----------------------------|------------------------------|--|--|
| Benzene(71-43-2) | X | X | X | | 6.4 µg/day (oral); 13 µg/day (inhalation) | 24 µg/day (oral); 49 µg/day (inhalation) |
| Toluene(108-88-3) | | X | | | | 7000 µg/day |
| lead/lead compounds() | X | X | X | X | 15 µg/day | 0.5 µg/day |
| Nickel compounds(trade secret) | X | | | | | |

VISCOSITY UNITEK 3000LS Diesel Engine Oil SAE 15W-40 CK-4

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

SECTION 16: Other information

Revision date : 12/03/2020

Data sources : ACGIH (American Conference of Government Industrial Hygienists). European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. NIOSH Occupational Health Guide for chemical Substances - Vol. II, September, 1978. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

Other information : None.

Full text of H-statements:

| | |
|------|--|
| H315 | Causes skin irritation. |
| H318 | Causes serious eye damage. |
| H411 | Toxic to aquatic life with long lasting effects. |


Abbreviations and acronyms:

| | |
|--|---|
| | ACGIH (American Conference of Government Industrial Hygienists) |
| | ATE: Acute Toxicity Estimate |
| | CAS (Chemical Abstracts Service) number |
| | CLP: Classification, Labelling, Packaging. |
| | EC50: Environmental Concentration associated with a response by 50% of the test population. |
| | GHS: Globally Harmonized System (of Classification and Labeling of Chemicals). |
| | LD50: Lethal Dose for 50% of the test population |
| | OSHA: Occupational Safety & Health Administration |
| | TSCA: Toxic Substances Control Act |
| | STEL: Short Term Exposure Limits |
| | TWA: Time Weighted Average |

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Indication of changes:
Product identifier.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.