



VISCOSITY UNITEK™ MG Diesel Engine Oil SAE 30

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR Issue date:
11/17/2020 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : VISCOSITY UNITEK™ MG Diesel Engine Oil SAE 30

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Lubricant
Restrictions on use : No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

Viscosity Oil Company
600 H Joliet Road
Willowbrook, IL 60527
T 630-850-4000 - F 630-850-4022

Importer

Viscosity Oil Company
1918 Boul.Saint-Regis
Dorval, QC H9P 1H6 - Canada

1.4. Emergency telephone number

Emergency number : (800) 424-9300
CHEMTREC (24 HOURS)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Not classified

2.2. Label elements

GHS labelling

No labelling applicable

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	% (w/w)	GHS classification
Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO < 3%)	(CAS.No.) 64742-65-0	60 - 70	Asp. Tox. 1, H304
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts	(CAS.No.) 84605-29-8	0.5 - 1.5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

VISCOSITY UNITEK™ MG Diesel Engine Oil SAE 30

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects after inhalation : Inhalation of vapours may cause respiratory irritation.
Symptoms/effects after skin contact : Repeated or prolonged skin contact may cause dermatitis and defatting.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Burning produces irritating, toxic and noxious fumes.
Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid all eye and skin contact and do not breathe vapour and mist.

6.1.1. For non-emergency personnel

- Protective equipment : Refer to section 8.2.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Refer to section 8.2.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Avoid all eye and skin contact and do not breathe vapour and mist.
Hygiene measures : Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep only in the original container in a cool well ventilated place.
Incompatible products : Strong oxidizers.
Incompatible materials : Sources of ignition. Direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

VISCOSITY UNITEK™ MG Diesel Engine Oil SAE 30

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO < 3%) (64742-65-0)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ oil mist
ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³ oil mist
OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)		
Not applicable		

8.2. Exposure controls

Appropriate engineering controls	: Avoid creating mist or spray. Avoid splashing. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Either local exhaust or general room ventilation is usually required.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Wear suitable gloves resistant to chemical penetration. Nitrile rubber gloves.
Eye protection	: In case of splashing or aerosol production: protective goggles.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. Approved organic vapour respirator.
Environmental exposure controls	: Prevent leakage or spillage.
Other information	: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: amber
Odour	: petroleum
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 235 °C
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: < 1 mm Hg
Relative vapour density at 20 °C	: > 1
Relative density	: 0.88
Solubility	: Negligible. Water: 0 - 1 %
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 90 mm ² /s @ 40 °C
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

VISCOSITY UNITEK™ MG Diesel Engine Oil SAE 30

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong oxidizers.

10.6. Hazardous decomposition products

hydrocarbons. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Inhalation; Skin and eye contact

Acute toxicity : Not classified

Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO < 3%) (64742-65-0)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)	
LD50 oral rat	3100 mg/kg
LD50 dermal rat	> 2002 mg/kg
LC50 Inhalation - Rat	> 2.3 mg/l/4h
ATE (oral)	3100 mg/kg bodyweight

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified.

(Component. Not irritating to rabbits on ocular application)

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

Symptoms/effects after inhalation : Inhalation of vapours may cause respiratory irritation.

Symptoms/effects after skin contact : Repeated or prolonged skin contact may cause dermatitis and defatting.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No ecotoxicological data about this product are known.

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)	
LC50 fish 1	4.5 mg/l
EC50 crustacea	23 mg/l
ErC50 (algae)	21 mg/l
NOEC (acute)	1.8 mg/l
NOEC chronic crustacea	0.8 mg/l

12.2. Persistence and degradability

VISCOSITY UNITEK™ MG Diesel Engine Oil SAE 30	
Persistence and degradability	Not established.
Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO < 3%) (64742-65-0)	
Persistence and degradability	Not established.

VISCOSITY UNITEK™ MG Diesel Engine Oil SAE 30

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)

Biodegradation	1.5 % 28 days
----------------	---------------

12.3. Bioaccumulative potential

VISCOSITY UNITEK™ MG Diesel Engine Oil SAE 30

Bioaccumulative potential	Not established.
---------------------------	------------------

Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO < 3%) (64742-65-0)

Bioaccumulative potential	Not established.
---------------------------	------------------

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)

Log Kow	0.56
---------	------

12.4. Mobility in soil

VISCOSITY UNITEK™ MG Diesel Engine Oil SAE 30

Ecology - soil	Not established.
----------------	------------------

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated.

Transportation of Dangerous Goods

Not regulated.

Transport by sea

Not regulated.

Air transport

Not regulated.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)

SARA Section 313 - Emission Reporting	1 % N982 Zinc compounds
---------------------------------------	-------------------------

15.2. International regulations

CANADA

Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO < 3%) (64742-65-0)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO < 3%) (64742-65-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

VISCOSITY UNITEK™ MG Diesel Engine Oil SAE 30

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations, Canada HPR

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Distillates (petroleum), solvent-dewaxed heavy paraffinic (DMSO < 3%) (64742-65-0)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on Taiwan National Chemical Inventory
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts (84605-29-8)

Not listed on the Inventory of Existing Chemical Substances of China (IECSC).
Listed on Taiwan National Chemical Inventory
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm.

SECTION 16: Other information

Data sources : ACGIH (American Conference of Government Industrial Hygienists). European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. NIOSH Occupational Health Guide for chemical Substances - Vol. II, September, 1978. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

Other information : None.


Full text of H-statements:

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H411	Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

	ACGIH (American Conference of Government Industrial Hygienists)
	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	OSHA: Occupational Safety & Health Administration
	TSCA: Toxic Substances Control Act
	STEL: Short Term Exposure Limits
	TWA: Time Weighted Average

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.
NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.